

Model 4069LE

SCISSOR LIFTS



MORE ECONOMIC

- Electric power for zero emissions and near-silent running indoors.

MORE PRODUCTIVE

- Boost efficiency with direct electric drive.

MORE ACCESS

- Enjoy enhanced versatility with true multi-terrain capability.

SMART DESIGN

- Enjoy industry leading upcycles so you can work longer with higher productivity.

Standard Features

- 0.91 m roll-out deck extension
- Fold-down handrails
- Self-closing gate
- Removable platform console box
- Lanyard attach points
- Full proportional drive joystick control with integral thumb steer switch
- Proportional lift/lower speed control
- Joystick enable for lift and drive
- Load sensing system
- Two speed drive selection
- Two Wheel Direct Electric Drive
- 8 x 6V 370 A/hr deep cycle batteries
- Automatic traction control
- Programmable "Personality" settings
- On-board self-diagnostic testing
- Detachable battery compartments
- 20 amp automatic battery charger
- Automatic rear wheel brakes
- Sculptured steel hoods
- 3 degree tilt alarm and indicator light
- Steel scissor guards
- Oscillating rear axle
- Lifting/tie down lugs
- Lubrication free scissor arm bushings
- Scissor maintenance prop
- AC cable to platform
- Ground control selector switch with key lock
- Battery condition indicator
- Hour meter
- Horn
- Manual descent pull cable

Standard Specifications

- Tyres (non-marking)
- Drive Motors
- Batteries
- Charger (120/240V - 50/60HZ)
- Hydraulic System
- 240/55-17.5
- Dual Electric Traction
- 8 x 6V 370 A/hr
- 20 Amp SCR Automatic
- 32 L

Accessories & Options

- Hydraulic levelling jacks
- 13mm air line to platform
- 390 A/hr AGM Batteries
- All motion alarm
- Descent alarm
- Alarm package ¹
- Platform work-lights
- Amber strobe light
- Euro Plug & Socket
- Synthetic Biodegradable Hydraulic Oil
- Special paint colour

¹ Includes all-motion alarm and amber strobe light.



0800 085 3709
WWW.AERIALPLATFORMS.CO.UK

HIRE NOW!

Aerial Platforms Ltd, Denebrook Court, Greenfold Way, Leigh, WN7 3XJ

Model 4069LE

SCISSOR LIFTS

Performance

- Working Height 14.19 m
- Platform Height — Elevated 12.19 m
 - A. Stowed Height 2.80 m
 - B. Platform Railing Height 1.10 m
 - C. Stowed Height (Rails Folded) 2.04 m
- D. Platform Size (W X L) 1.65 m x 2.92 m
- E. Deck Extension 0.91 m
- F. Overall Width 1.75 m
- G. Overall Length 3.07 m
- H. Wheelbase 2.32 m
- I. Ground Clearance 0.20 m
- Platform Capacity 360 kg
- Capacity on Deck Extension 120 kg
- Lift/Lower Time 54/50 sec.
- Maximum Drive Height 9.14 m
- Machine weight 5,300 kg
- Maximum Ground Bearing Pressure 4.3 kg/cm²
- Drive Speed — Lowered 4.8 km/h
- Gradeability 35%
- Turning Radius — Inside 2.29 m
- Turning Radius — Outside 4.88 m



Dimensions

