

MORE ECONOMIC

 Cut fuel consumption and operating costs with variable engine control.

MORE PRODUCTIVE

 Start work guicker with industry leading elevation time.

(* 50% faster compared with previous model. Actual timings may vary.) Carry more tools and materials and be able to work longer with 250 kg basket weight capacity.

MORE ACCESS

• Increase your work envelope with more horizontal reach. (*Compared with previous model.)

SMART DESIGN

• Reduce maintenance with DuraTough turntable hood. High impact resistance and protects components.

Standard Features

- 1.24 m (4ft 1in) Articulating Jib
- 0.76 m x 1.83 m (30in x 72in) Platform
- 180 Degree Hydraulic Platform Rotator
- Platform Console Machine Status Light Panel*
- · AC cable to Platform
- 5 Degree Tilt Alarm/Indicator Light
- · Swing Out Engine Module
- Dura Tough gull-wing turntable hoods
- 12V-DC Auxiliary Power
- Hourmeter
- Interactive Display at Ground Controls
- Control ADE® Advanced Design Electronics System
- · Lifting/Tie Down Lugs
- Horn
- · Four-Wheel Hydrostatic Drive
- · Oscillating Axle

- Cast Aluminum Control Box
- · Motion Alarm
- · Platform Tool Tray
- · Side entry with drop bar mid rail
- · Multiple function operation
- · Full proportional drive joystick control with integral thumb steer switch
- Full proportional main boom and swing joystick control
- Multiple speed control for telescope and platform rotate
- Selectable creep speed on drive / lift and swing functions
- · Load sensing system
- Engine distress warning/shut down system
- Ground control selector switch with key lock
- Dual rated platform capacity up to 450 kg
- JLG Skyguard active system
- * Provides indicator lights at platform control console for system distress, low fuel, 5 degree tilt light, and foot switch status.

Standard Specifications

Power Source

- Diesel Engine
- · Fuel Tank Capacity Hydraulic System
- · System Capacity
- Tank Capacity
- · Auxiliary Power Tyres
- Standard
- · Optional

Deutz D2.3 L3 Stage IIIA 36.4 kW 60.5 L

144 L

60.5 L 12V-DC

33/1550 x 16.5 foam Filled tyres 315/55 D20 foam filled tyres Non-Marking Tires

Accessories & Options

- 0.76 m x 1.22 m slide bar side entry
- 0.76 m x 1.22 m Self closing inward swing gate
- 0.76 m x 1.52 m slide bar side entry platform
- 13 mm airline to platform
- Flashing Amber Beacon
- Hostile Environment Kit ¹
- · Light Package
- · Platform Worklights
- Skypower 7,500W generator package
- PipeRack
- · Catalytic exhaust purifier
- On-board 4,000W generator

- Skyguard beacon (ILOS)
- · Tow package
- Cold weather package
- · Generator hourmeter
- · Hydraulic Oil Cooler
- Synthetic Biodegradable Hydraulic Oil
- All motion alarm
- · Head & Tail Lights
- · Euro Plug & Socket
- Special paint colour
- Foam filled (flip for ship) 315/55 D20
- Non Mark FF (flip for ship) 315/55 D20

1 Includes boom wipers, cylinder bellows and console cover

Note: Some options may increase lead time, and some option combinations may not be available



0800 085 3709

HIRE NOW! WWW.AERIALPLATFORMS.CO.UK



Performance

• Working Height 15.77 m · Working Outreach 8.27 m · Up and Over Height 7.3 m

• Swing 355 Degrees Non-Continuous

 Platform Capacity 250 kg • Platform Size 0.76 x 1.83 m 180 Degrees Hydraulic · Platform Rotator

• Dimensions:

0.76 m x 1.83 m A. Platform Size B. Overall Width 2.35 m C. Tailswing (working condition) Zero 2.27 m D. Stowed Height E. Stowed Length 6.58 m F. Wheelbase 2.36 m G. Ground Clearance 0.42 m 1.24 m

144 Degrees (+76, -69) • Range of Articulation


 Weight ^{1/2} 6,495 kg • Max Ground Bearing Pressure 2 4 kg/cm² • Drive Speed 6.8 km/h Gradeability 45% Axle Oscillation 10 cm

• Turning Radius


Inside 2.06 m Outside 4.78 m

1 Certain options or country standards may increase weight and/or dimensions

Reach Diagram



Dimensions





0800 085 3709

WWW.AERIALPLATFORMS.CO.UK



² With Standard tires