



0800 085 3709

WWW.AERIALPLATFORMS.CO.UK

HIRE NOW!


LGMG Electric - Articulating Boom Lift


SPECIFICATIONS


MODELS	A14JE (A4	15JE)
Measurements	Metric	Imperial
Work Height Max.	15.8m	51'10''
Platform Height Max.	13.8m	45'3"
Horizontal Outreach	7.81m	25'7"
Up and Over Height	7.26m	23'10''
Platform Length	1.83m	6'
Platform Width	0.76m	2'6"
Stowed Length	6.66m	21'10''
Length-Transport (jib tucked)	5.67m	18'7"
Stowed Width	1.8m	5'11''
© Stowed Height	1.98m	6'6"
Height-Transport	2.54m	8'4"
• Wheelbase	2.03m	6'8"
■ Ground Clearance	0.24m	9"
PRODUCTIVITY		
Max. Platform Occupancy	2	
Platform Capacity	230kg	510 lbs
Turning Radius-Inside	1.83m	6'
Turning Radius-Outside	4.1m	13'5"
Turntable Rotation	355°	355°
Max.Slope	3°/3°	3°/3°
Max. Drive Speed (Stowed)	4.8km/h	3mph
Max. Drive Speed (Raised)	1km/h	0.62mph
Gradeability	30%	30%
Tire Type	Foam-filled	
Tire Size	9-14.5	
POWER		
Lead-acid Battery	48V 390Ah	
Lithium Battery (A14JE-Li)	48V 280Ah	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	30L	7.9gal
WEIGHT		
Machine Weight	7500kg	16535 lbs

STAN DARD FE ATURES		
Proportional control	Platform auto-leveling system	
Horn/Hour meter	On-board diagnostic system	
Tilt alarm with lift cut-out	Rear-wheel drive and break	
Emergency stop button	Over tilt protection system	
Anti-collision protection	Overload sensing system	
Full-height drive	Descent alarm with flashing beacon	
Telematics connector	Platform tool box	
Foam-filled tires		

OPTIONAL	
Telematics	Solid tires
AC power to platform	Solid non-marking tires
Biodegradable hydraulic oil	







Please contact LGMG or a local dealer for more details. LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only. This brochure comes into effect in May, 2023.



0800 085 3709 WWW.AERIALPLATFORMS.CO.UK

