



# Electric scissor lift JCPT1412DC



**0800 085 3709**

[WWW.AERIALPLATFORMS.CO.UK](http://WWW.AERIALPLATFORMS.CO.UK)

Aerial Platforms Ltd, Denebrook Court, Greenfold Way, Leigh, WN7 3FZ

**HIRE NOW!**

 PART OF THE CENTURION GROUP

# Electric scissor lift JCPT1412DC

## STANDARD EQUIPMENT

- Proportional controls
- Automatic pothole protection
- Self-lock gate on platform
- Drivable at full height
- Non marking tires
- 2WD
- Automatic brakes system
- Emergency lowering system
- Emergency stop buttons
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All motion alarm
- Horn
- Hour meter
- Safety brackets
- Forklift pockets
- Folding guardrails
- Extended platform
- Charger protection
- Flashing beacon

## OPTIONS

- Overload sensor with alarm
- AC power to the platform
- Platform work lights
- Airline to the platform

## SPECIFICATIONS

|   | JCPT1412DC     |
|---|----------------|
|  S.W.L.                             | 320 kg         |
|  S.W.L. on extension                | 113 kg         |
|  Maximum workers                    | 3              |
|  Working height                    | 13,8 m         |
|  Platform floor height            | 11,8 m         |
|  Overall length                   | 2,48 m         |
|  Overall width                    | 1,19 m         |
|  Overall height (rails up/down)   | 2,59/2,05 m    |
|  Platform size                    | 2,27x1,12 m    |
|  Platform extension size          | 0,90 m         |
|  Ground clearance (stowed/raised) | 0,1/0,019 m    |
|  Wheelbase                        | 1,87 m         |
|  Turning radius (inside/outside)  | 0/2,20 m       |
|  Drive motors                     | 24 V / 1,5 kw  |
|  Lifting motors                   | 24 V / 3 kw    |
|  Travel speed (stowed/raised)     | 4,0/0,8 km/h   |
|  Up/Down speed                    | 84/38 sec      |
|  Batteries                        | 4x6 V / 210 Ah |
|  Integrated charger               | 24 V / 25 A    |
|  Gradeability                     | 25 %           |
|  Maximum working slope            | 1,5-3°         |
|  Driving wheels                   | Ø 381x127 mm   |
|  Weight                           | 2880 kg        |

