



**Electric scissor lift**  
**JCPT1612DC**



**0800 085 3709**

[WWW.AERIALPLATFORMS.CO.UK](http://WWW.AERIALPLATFORMS.CO.UK)

Aerial Platforms Ltd, Denebrook Court, Greenfold Way, Leigh, WN7 3FZ

**HIRE NOW!**

 PART OF THE CENTURION GROUP

# Electric scissor lift JCPT1612DC

## STANDARD EQUIPMENT

- Proportional controls
- Automatic pothole protection
- Self-lock gate on platform
- Drivable at full height
- Non marking tires
- 2WD
- Automatic brakes system
- Emergency lowering system
- Emergency stop buttons
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All motion alarm
- Horn
- Hour meter
- Safety brackets
- Forklift pockets
- Folding guardrails
- Extended platform
- Charger protection
- Flashing beacon

## OPTIONS

- Overload sensor with alarm
- AC power to the platform
- Platform work lights
- Airline to the platform

## SPECIFICATIONS

### JCPT1612DC

	S.W.L.	<b>200 kg</b>
	S.W.L. on extension	<b>113 kg</b>
	Maximum workers	<b>2</b>
	Working height	<b>15,7 m</b>
	Platform floor height	<b>13,7 m</b>
	Overall length	<b>2,84 m</b>
	Overall width	<b>1,25 m</b>
	Overall height (rails up/down)	<b>2,59/2,05 m</b>
	Platform size	<b>2,64x1,12 m</b>
	Platform extension size	<b>0,90 m</b>
	Ground clearance (stowed/raised)	<b>0,1/0,019 m</b>
	Wheelbase	<b>2,22 m</b>
	Turning radius (inside/outside)	<b>0/2,65 m</b>
	Drive motors	<b>24 V / 1,5 kw</b>
	Lifting motors	<b>24 V / 4,5 kw</b>
	Travel speed (stowed/raised)	<b>4,0/0,8 km/h</b>
	Up/Down speed	<b>88/60 sec</b>
	Batteries	<b>4x12 V / 300 Ah</b>
	Integrated charger	<b>24 V / 25 A</b>
	Gradeability	<b>25 %</b>
	Maximum working slope	<b>2-3°</b>
	Driving wheels	<b>Ø Ø 381x127 mm</b>
	Weight	<b>3180 kg</b>

